



Barstool with solid beech seat and back, upholstered seat pad and 4-legs solid beech wood base.

0.34 m3 7.5 kg 12.01 Ft 16.53 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	1,090	780	505	465

Frame	4-legged solid beech wood base.
Seat	Upholstered seat cushion on solid beech.
Back	Solid beech.
Accesories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1 Soft-fiber
 Jacquard One
 Jacquard Three
 Citadel
 Sand
 Era
 Gravity
 Rivet
 Urban
- 2 Jacquard Two
 Solid & Stripes
 Loom One
 Circular One Pure Eco
- 3 Jacquard Four
 Medley
 Revive 1
 Natte
 Main Line Flax
 Loom Two
 Mezzo

- 4 Jacquard 4 Special
 Nexus
 Field 2
 Floyd
 Remix 3
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5 Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6 Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7 Canvas 2
 Rime
 Select
 Clara 2
- 8 Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9 Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
 2 Silvertex
 3 Maglia
 4 Dolce
- 8 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
- 9 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
- 10 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired

- 11 Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Upholstery

- Leather / Piel
- L1 High grade cow leather
 Piel de vaca de 1ª categoría
- L3 Polished full grain leather
 Plena flor pulida
- L6 Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Leather

Wood finish
 Beech



Premium finish
 and wood
 lacquers



- RESISTANCE AND
 QUALITY
- UNE-EN 16139:2013
- FIREPROOF
- UNE-EN 1021-1:2006
 B.S. 5852 Part 2 Crib V
 UNI 9175 M-1
 California Tech.Bulletin 117
 BKZ 5.2

- SUSTAINABILITY
- FSC
 ISO 14001
 level® 2 certified to ANSI/BIFMA e3 Standard